



Liby's Stripe Right

Chris Liby

260-273-1729 Libystripe@gmail.com

Thank you for choosing & putting your trust in Liby's Stripe Right & Sealcoating. We use high quality Sealmaster sealcoat products. Our sealer contains 100 lbs of sand for every 100 gallons of sealer. This helps with traction and increased longevity of the sealer. Top Tuff is also added to the sealer to improve surface toughness and helps to resist oils, fuels and grease as well as helps to reduce power steering marks.

Here are some frequently asked questions:

Drying Time

Please allow at least 24 hours of drying time before driving on your newly sealed driveway or parking lot. If it looks wet, it is! You may walk on it as soon as it looks dry. Please allow longer drying time for humid or shady conditions.

Cracks

We may have filled cracks in your driveway before applying sealer. Hot rubberized crack filler is used to fill large cracks and may not be smooth with the asphalt. This is normal.

What to expect

After sealing you may notice what appears to be marking from tires of your car. These are called power steering marks and can be expected for the first few weeks. This is caused from the sand in the sealer loosening at the top of the coating. These marks should disappear in time. Avoid making sharp turns to reduce these marks.

Edging

A difference in the appearance of the sealer may be noticed around concrete, fences or other structures such as the house or garage. This was caused by hand edging which is done to avoid getting sealer material on your property.

We take pride in our work and treat your investment as if it is our own. Please contact us with any questions or concerns. Thank you for your business!!